



## Hi-Rate Commercial Bobbin wound Sand Filter



- Filter tank made from polyester and non-corrosive fiberglass..
- All internal components and connections are injection moulded PVC.
- Extra deep sand bed allows for efficient filtration and backwashing.
- Designed to be assembled with Butterfly valve. 2x3" oil pressure gauges are included.
- Large service opening (manhole) gives easy access to inside part of filter (optional).
- Sight glass made of top quality material (optional).
- Maximum operating pressure 2.5kgs/cm<sup>2</sup>
- UV-resistant surface enables the filters to work in the direct sunlight.
- 4kgs/cm<sup>2</sup>. Available on demand.
- Available filter colors



**Best choice for efficient water filtration of a public swimming pool or an industrial water treatment system.**



3 inch Multi port-valve

Code	Description	Tank dia B (mm)	Height A (mm)	Valve height C (mm)	Valve port size (mm)	Filter area (m <sup>2</sup> )	Design flow (m <sup>3</sup> /h)	Silica sand (kgs)
CX-10601	1200mm (48")	1200	1450	900	90	1.13	52	1200
CX-10602	1400mm (56")	1400	1650	1000	110	1.54	69	1900
CX-10603	1600mm (64")	1600	1800	1100	110	2.00	80	2600
CX-10604	1800mm (72")	1800	1900	1300	140	2.70	125	3600
CX-10605	2000mm (80")	2000	2150	1350	160	3.14	157	5100
CX-10606	2350mm (94")	2350	2350	1500	200	4.30	217	7600
CX-10607	2500mm (100")	2500	2650	1600	250	4.90	250	9200